

# ADLERTECH SYSTEMS

## RM 901

### Video Receiver

#### SPECIFICATIONS

<b>General:</b>	
Standard Frequency Bands	S Band or L Band (other Frequency Band are support) Up to 200 MHz tuning range
Nominal Frequency Stability	± 0.002 %
Output Impedance	Nominal 75 ohms
VSWR	1.5:1
<b>Power:</b>	
Voltage	12 Volts ± 2 V as standard. (Other options including 28 V DC)
Output Amplitude	Up to 5 Volts p-p
<b>Mechanical:</b>	
Maximum Dimensions	Standard 85 mm wide 105 mm long and 35 mm high excluding antenna connector
RF Output Connector	SMA as standard. SMB and SMC Options available
<b>Standard Environment:</b>	<b>Application specific environmental testing and proving can be performed</b>
Normal Operating Temp	-20 deg Centigrade to +75 deg Centigrade case temperature
Normal Vibration	Greater than 5 g sine, 0.1g 2 random, 20Hz to 2000Hz, in any axis
Normal Shock	10g for 1 ms in three mutually perpendicular axes
Normal Acceleration	10g in three mutually perpendicular axes

**US Government Export License Authorization Not Required**

*All specifications are subject to change without notice.*

#### ADLERTECH SYSTEMS PTE LTD

56A KALLANG PUDDING ROAD #07-00. SINGAPORE 349329

Tel: (65) 6747 4636 Fax: (65) 6747 6919

EMAIL: sales@adlertechsystems.com